# EAST Search History

| Ref # | Hits | Search Query | DBs | Default Operator | Plurals | Time Stamp |
|---|---|---|---|---|---|---|
| L1 | 169 | ((comput$5 or generat$5)near(shared or secret)same(d$ffie$hellman)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:07 |
| L2 | 35 | L1 ((privacy or encod$5 or encryption)adj(key))((authenticat$5 )adj (key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:03 |
| L3 | 24 | L2 (server or SNMP) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 16:49 |
| L4 | 24 | L3 (public) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 16:50 |
| L5 | 21 | L3 (random) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 16:51 |
| L6 | · 1 | ((SNMP)same(d$ffie$hellman)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:08 |
| L7 | 68 | ((SNMP)(d$ffie$hellman)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:38 |
| L8 | 14 | L7 ((privacy or encod$5 or encryption)adj(key))((authenticat$5 )adj (key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:03 |
| L9 | 19 | L7 ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5) adj (key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:11 |
| L10 | 1 | "6157721".pn. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:05 |
| L11 | 476 | ((comput$5 or generat$5)near(shared or secret)same(exchang$5)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:11 |

# EAST Search History

| L12 | 3 | L11((SNMP)(d$ffie$hellman)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:09 |
|-----|-----|-----|-----|-----|-----|-----|
| L13 | 208 | L11((d$ffie$hellman)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:23 |
| L14 | 121 | L13 (random same public) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:10 |
| L15 | 104 | L14 (server or network or manager)(user or client or agent) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:10 |
| L16 | 121 | L14((comput$5 or generat$5)near(shared or secret)same(exchang$5)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:11 |
| L17 | 45 | L16((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5)adj (key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:38 |
| L18 | 848 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5)adj (key))(initial)(secret) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:38 |
| L20 | 14 | L19(d$ffie$hellman) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:38 |
| L21 | 23 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5)adj (key))(initial)(secret)(SNMP) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:41 |
| L22 | 0 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5)adj (key))(initial)(secret)(SNMP).ab. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:41 |
| L23 | 3 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5)adj (key))(SNMP).ab. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:45 |
| L24 | 5 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5)adj (key))(SNMP).clm. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:46 |

| L25 | 48 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5) adj (key))(SNMP) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:52 |
|---|---|---|---|---|---|---|
| L26 | 24 | L25 ((secret)adj(key or value)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:47 |
| L27 | 86 | ((shared)adj(secret))(SNMP)(secret adj key) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:50 |
| L28 | 86 | ((shared)adj(secret or value))(SNMP)(secret adj key) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:52 |
| L29 | 0 | ((shared)adj( value))(SNMP)(secret adj key) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:52 |
| L30 | 33 | ((shared)near( value))(SNMP)(secret adj key) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 17:52 |
| L31 | 30 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5 or integr$5)adj (key))(SNMP)((shared or secret)near(key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:11 |
| L32 | 1258 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5 or integr$5)adj (key))((shared or secret)near(key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:11 |
| L33 | 189 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5 or integr$5)adj (key))((shared or secret)near(key))(password)(client near server) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:11 |
| L34 | 73 | ((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5 or integr$5)adj (key))((shared or secret)near(key))((generat$5)same (password)same(key))(client near server) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:25 |
| L35 | 7 | L34(client near server).ab. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:19 |

| L36 | 315 | (password)(key)(secret)(string or value)(SNMP) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:16 |
|-----|-----|---|---|---|---|---|
| L37 | 0 | ((generat$5)adj(password)same(secret))(key)(string or value)(SNMP)(authenticat$5) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:19 |
| L38 | 0 | ((generat$5)adj(password)same(secret))(key)(SNMP)(authenticat$5) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:18 |
| L39 | 0 | ((generat$5)adj(password)same(secret))(SNMP) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:18 |
| L40 | 86 | ((generat$5)adj(password)same(secret))(key)(string or value)(authenticat$5) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:22 |
| L41 | 8 | L40(client near server) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:19 |
| L42 | 132 | ((generat$5)adj(password)same(secret)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:22 |
| L43 | 15 | ((generat$5)adj(password)same(secret)).ab. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:22 |
| L44 | 750 | ((password)(d$ffie$hellman)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:24 |
| L45 | 618 | (((password) same(key or secret or shared))(d$ffie$hellman)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:25 |
| L46 | 406 | L45 initial | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:26 |
| L47 | 132 | L46((privacy or encod$5 or encrypt$5)adj(key))((authenticat$5 or integr$5)adj (key))((shared or secret)near(key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:25 |

| L48 | 125 | L47((initial$5)same(key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND. | ON | 2007/03/05 18:30 |
|---|---|---|---|---|---|---|
| L49 | 408 | ((initial$5)same(key))(d$ffie$hellman or snmp)(password)(key)(secret)(shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:31 |
| L50 | 187 | ((initial$5)same(key))(d$ffie$hellman or snmp)((generat$5)adj(key))(password)(key)(secret)(shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:32 |
| L51 | 24 | ((initial$5)same(key))(d$ffie$hellman or snmp)((generat$5)adj(password or PIN))(key)(secret)(shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:35 |
| L52 | 0 | ((initial$5)same(key))(snmp).ab. ((generat$5)adj(password or PIN))(key)(secret)(shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:35 |
| L53 | 3 | ((initial$5)same(key))(snmp)((generat$5)adj(password or PIN))(key)(secret or shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:36 |
| L54 | 10 | ((initial$5)(key))(snmp)((generat$5)adj(password or PIN))(key)(secret or shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:36 |
| L55 | 11 | (snmp)((generat$5)adj(password or PIN))(key)(secret or shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:37 |
| L56 | 12 | (snmp)((generat$5)adj(password or PIN)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:38 |
| L57 | 286 | (713/184).CCLS. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | OR | OFF | 2007/03/05 18:38 |
| L58 | 67 | L57((generat$5)adj(password or PIN)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:38 |
| L59 | 32 | L57((generat$5)adj(password or PIN)).clm. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 18:55 |

| | | | | | | |
|---|---|---|---|---|---|---|
| L60 | 5 | ((generat$5)adj(password or PIN))((readable) adj (password or PIN)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:19 |
| L61 | 6 | ((generat$5 or human)near(password or PIN))((readable) adj (password or PIN)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:38 |
| L62 | 1 | "5841864".pn. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:38 |
| L63 | 1 | "5825300".pn. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:38 |
| L64 | 2 | L62 or L63 | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:39 |
| L65 | 1 | L64 (password or PIN or passphrase) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:40 |
| L66 | 1 | L64 (password or PIN or passphrase)(shared) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:41 |
| L67 | 413 | (password or PIN or passphrase)((shared)adj(secret))(snmp or diffie$hellman) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:42 |
| L68 | 248 | (password or PIN or passphrase)((shared)adj(secret))(snmp or diffie$hellman)(readable) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:42 |
| L69 | 247 | (password or PIN or passphrase)((shared)adj(secret))(snmp or diffie$hellman)(readable)(key) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:43 |
| L70 | 215 | L69(password or PIN or passphrase)same(((shared)adj(secret))or (key)) | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:44 |
| L71 | 44 | L70((password or PIN or passphrase)(((shared)adj(secret))or (key))).clm. | US-PGPUB; USPAT; EPO; JPO; IBM_TDB | AND | ON | 2007/03/05 19:44 |

# Google Scholar BETA  Advanced Scholar Search  <u>Advanced Search Tips</u> | <u>About Google Scholar</u>

**Find articles** with **all** of the words    `snmp generates key shared`    `10 results ▼`    Search Schola

with the **exact phrase**

with **at least one** of the words    `password or PIN`

**without** the words

where my words occur    `anywhere in the article ▼`

**Author**    Return articles written by

     e.g., *"PJ Hayes"* or *McCarthy*

**Publication**    Return articles published in

     e.g., *J Biol Chem* or *Nature*

**Date**    Return articles published between `1992` — `1999`

     e.g., *1996*

**Subject Areas**

◉ Return articles in all subject areas.

○ Return only articles in the following subject areas:

- ☐ Biology, Life Sciences, and Environmental Science
- ☐ Business, Administration, Finance, and Economics
- ☐ Chemistry and Materials Science
- ☐ Engineering, Computer Science, and Mathematics
- ☐ Medicine, Pharmacology, and Veterinary Science
- ☐ Physics, Astronomy, and Planetary Science
- ☐ Social Sciences, Arts, and Humanities

©2007 Google

Google Scholar BETA

| snmp generates key shared password OR or ( | 1992 | - | 1999 | Search | Adv Scl Scl |

Lowercase **"or"** was ignored. Try **"OR"** to search for either of two terms. [details]

**Scholar** All articles <u>Recent articles</u> Results **1 - 10** of about 593 for **snmp generates key shared password**

**All Results**

<u>W Stallings</u>
<u>G Tsudik</u>
<u>R Molva</u>
<u>Y Yemini</u>
<u>O Schelen</u>

### SNMP and SNMPv2: the infrastructure for network management - group of 4 »
W Stallings - Communications Magazine, IEEE, 1998 - ieeexplore.ieee.org
... SN M Pvl Table 1 lists the **key** RFCs that define SNMPv1. ... Table 2. **SNMP** message and ...
IEEE Communications Magazine March 1998 41 to **generate** multiple transactions. ...
<u>Cited by 109</u> - <u>Related Articles</u> - <u>Web Search</u> - <u>BL Direct</u>

### SNMPv3: A Security Enhancement for SNMP - group of 16 »
W Stallings - IEEE Communications Surveys, 1998 - comsoc.org
... to **generate** an authentication **key** and one to **generate** a distinct ... defined in RFC 2274 as a secret **key shared** between a user and one authoritative **SNMP** engine. ...
<u>Cited by 41</u> - <u>Related Articles</u> - <u>Cached</u> - <u>Web Search</u>

### Method of protected distribution of keying and certificate material - group of 2 »
EW Bathrick, JW Garber, CC Huang, KC Kung, TE ... - US Patent 5,825,300, 1998 - Google Patents
... **GENERATE** CERTIFICATE SIGN CERTIFICATE **SNMP** SET CERTIFICATE CA PUBIC ... WRITE SNMPcfg
FILES (WITH KEYS ) **GENERATE** PUBLIC/ PRIVATE ... SAVE CERTIFICATE CA PUBLIC **KEY** ...
<u>Cited by 12</u> - <u>Related Articles</u> - <u>Web Search</u>

### Key derivation for network management applications - group of 3 »
U Blumenthal, NC Hien, B Wijnen - Network, IEEE, 1997 - ieeexplore.ieee.org
... of keys, a user must provide the **key** at login ... and the localized keys can be **generated** dynamically when ... minimal software installation — like an **SNMP** shell, or ...
<u>Cited by 12</u> - <u>Related Articles</u> - <u>Web Search</u> - <u>BL Direct</u>

### Apparatus and method for authentication and session key exchange in a communication system - group of 2 »
JT Klayman, LD Finkelstein, CL Clanton - US Patent 5,841,864, 1998 - Google Patents
... and communication protocol management (such as **SNMP** management). ... In summary, the
station 101 **generates** R and ... steps of: establishing a secret **key shared** by both ...
<u>Cited by 8</u> - <u>Related Articles</u> - <u>Web Search</u>

### Internet security architecture - group of 9 »
R Molva - Computer Networks, 1999 - cs.plu.edu
... 2) **key** generation with Diffie-Hellman: the server and the cli- ent **generate a shared** secret **key** using the Diffie-Hellman algorithm [14][15] and each other's ...
<u>Cited by 33</u> - <u>Related Articles</u> - <u>View as HTML</u> - <u>Web Search</u>

### The New SNMPv3 Proposed Internet Standards

# Google Scholar BETA

**Advanced Scholar Search**

| | | | |
|---|---|---|---|
| **Find articles** with **all** of the words | snmp readable secret diffie-he | 10 results ▾ | Search Schola |
| with the **exact phrase** | | | |
| with **at least one** of the words | password or PIN | | |
| **without** the words | | | |
| where my words occur | anywhere in the article ▾ | | |

**Author** Return articles written by
e.g., *"PJ Hayes"* or *McCarthy*

**Publication** Return articles published in
e.g., *J Biol Chem* or *Nature*

**Date** Return articles published between 1992 — 1999
e.g., *1996*

**Subject Areas**
⦿ Return articles in all subject areas.

○ Return only articles in the following subject areas:

☐ Biology, Life Sciences, and Environmental Science
☐ Business, Administration, Finance, and Economics
☐ Chemistry and Materials Science
☐ Engineering, Computer Science, and Mathematics
☐ Medicine, Pharmacology, and Veterinary Science
☐ Physics, Astronomy, and Planetary Science
☐ Social Sciences, Arts, and Humanities

©2007 Google

# Google Scholar BETA

| snmp readable secret diffie-hellman password | 1992 | - | 1999 | Search | Adv Scl Scl |

Lowercase **"or"** was ignored. Try **"OR"** to search for either of two terms. [details]

**Scholar** Results **1 - 4** of **4** for **snmp** <u>readable</u> <u>secret</u> diffie-<u>hellman</u> **password** OR or OR <u>PIN</u>. (0.07 seconds

**All Results**

P Amrozowicz

J Klayman

L Finkelstein

C Clanton

Motorola Inc.

### Apparatus and method for authentication and session key exchange in a communication system - group of 2 »
JT Klayman, LD Finkelstein, CL Clanton - US Patent 5,841,864, 1998 - Google Patents
... stations, and communication protocol management (such as **SNMP** management). ... The **secret** ...
their correspond- 65 key is generated using **Diffie-Hellman** key exchange ...
Cited by 8 - Related Articles - Web Search

### Routing in Communications Networks, Martha - group of 2 »
I Part - IBM SYSTEMS JOURNAL, 1995 - research.ibm.com
... a book on computer se- curity **readable** by a ... the **Diffie-Hellman** algorithm for **secret** key agreement ... Simple Network Management Protocol (**SNMP**), Digital Equipment ...
View as HTML - Web Search

### A Unix Streams Implementation of the Internet Protocol Security - group of 5 »
T Aalto - Helsinki University of Technology, September, 1996 - infiltrated.net
... database system used to map human-**readable** machine names ... data to be authenticated
and the **secret** key ... The Simple Network Management Protocol (**SNMP**) is a standard ...
Cited by 3 - Related Articles - View as HTML - Web Search

### Secure socket layer application program apparatus and method - group of 5 »
T Elgamal, KEB Hickman - US Patent 5,657,390, 1997 - Google Patents
... for encrypting information received from an application layer program; and computer **readable** pro -gram ... key encryption techniques using RSA and **Diffie-Hellman** ...
Cited by 90 - Related Articles - Web Search

| snmp readable secret diffie-hellman | Search |

Google Home - About Google - About Google Scholar

©2007 Google

Google Scholar BETA

Lowercase **"or"** was ignored. Try **"OR"** to search for either of two terms. [details]

**Scholar** All articles  Recent articles Results **1 - 10** of about **102** for **SNMP generates secret password** OR

**All Results**

W Stallings
G Tsudik
J Picazo
P Lee
R Zager

## Method of protected distribution of keying and certificate material - group of 2 »

EW Bathrick, JW Garber, CC Huang, KC Kung, TE ... - US Patent 5,825,300, 1998 - Google Patents

... **GENERATE** CERTIFICATE SIGN CERTIFICATE **SNMP** SET CERTIFICATE CA PUBIC KEY ... to a single
visit by using a **password** (shared **secret**) to **generate** the essential ...
Cited by 12 - Related Articles - Web Search

## SNMP and SNMPv2: the infrastructure for network management - group of 4 »

W Stallings - Communications Magazine, IEEE, 1998 - ieeexplore.ieee.org
... TRANSFER ENHANCEMENTS SNMPv1 can **generate** considerable traffic as ... some arbitrary
set of **SNMP** application munity functions as a **password** to authenticate ...
Cited by 109 - Related Articles - Web Search - BL Direct

## Key derivation for network management applications - group of 3 »

U Blumenthal, NC Hien, B Wijnen - Network, IEEE, 1997 - ieeexplore.ieee.org
... an **SNMP** shell, or a command-line interface to **SNMP**. ... A portable NMS does not require
any **secret** to be ... All the secrets are **generated** when required from the user ...
Cited by 12 - Related Articles - Web Search - BL Direct

## The New SNMPv3 Proposed Internet Standards

W Stallings, E **SNMP** - Links, 1998 - cisco.com
... Listens for notification messages, and **generates** response messages ... Each authoritative
**SNMP** engine is responsible for incrementing its ... **Secret**-Key Authentication. ...
Related Articles - Cached - Web Search

## SNMPv3: A Security Enhancement for SNMP - group of 16 »

W Stallings - IEEE Communications Surveys, 1998 - comsoc.org
... to **generate** an authentication key and one to **generate** a distinct ... is defined in RFC
2274 as a **secret** key shared between a user and one authoritative **SNMP** engine ...
Cited by 41 - Related Articles - Cached - Web Search

## Message authentication with one-way hash functions - group of 28 »

G Tsudik - ACM SIGCOMM Computer Communication Review, 1992 - portal.acm.org
... achieved, one of principals, say, A, **generates** a rando m ... The **secret** prefix method
was developed independently by ... in Simple Network Management Protocol (**SNMP**) [6 ...
Cited by 112 - Related Articles - Web Search - BL Direct

## Internet security architecture - group of 9 »

R Molva - Computer Networks, 1999 - cs.plu.edu
... two different key exchange methods: 1) key distribution with RSA (see [14][15] for

# Google Scholar BETA

**Scholar** All articles  Recent articles  Results **1 - 10** of about **2,300** for <u>**key** **initialization** **PIN** OR **password**</u>. (

**All Results**

<u>S HALEVI</u>

<u>D McGrew</u>

<u>A Aziz</u>

<u>G Tsudik</u>

<u>H KRAWCZYK</u>

### Public-**Key** Cryptography and **Password** Protocols - group of 18 »
S HALEVI, H KRAWCZYK - ACM Transactions on Information and System Security, 1999 -
portal.acm.org
... We use pseudorandom functions for **key** derivation as ... of protocols we omit an
**initialization** flow in ... 3.1 Encrypted **Password** Transmission We start by presenting ...
<u>Cited by 143</u> - <u>Related Articles</u> - <u>Web Search</u>

### Re-**initialization** of an iterated hash function secure **password** system over an insecure network ... - group of 2 »
MM Anderson - US Patent 5,751,812, 1998 - Google Patents
... whether re-**initialization** is needed, or the server could pair will therefore implement
a secure **password** technique. ... as the above-described S/**Key**™ system, in ...
<u>Cited by 14</u> - <u>Related Articles</u> - <u>Web Search</u>

### The Electronic Check Architecture - group of 3 »
MM Anderson - Financial Services Technology Consortium (FSTC) White Paper, ..., 1998 -
iclass.shufe.edu.cn
... enters a **PIN** to unlock an electronic checkbook card in the form of a smart card.
This card is a secure container for the payer's private signature **key**, and ...
<u>Cited by 13</u> - <u>Related Articles</u> - <u>Web Search</u>

### An empirical comparison of four **initialization** methods for the K-Means algorithm - group of 4 »
JM Pena, JA Lozano, P Larranaga - Pattern Recognition Letters, 1999 -
ingentaconnect.com
... literature that its performance depends upon two **key** points: initial ... the convergence
speed than the random **initialization** method ... User name **Password** Remember me. ...
<u>Cited by 88</u> - <u>Related Articles</u> - <u>Web Search</u>

### **Key** Establishment in Large Dynamic Groups Using One-Way Function Trees - group of 10 »
DA McGrew, AT Sherman - Manuscript, 1998 - networkassociates.com
... This construction is used by the one-time **password** system 7 and the ... 2. Tables 1 and
2 give the complexities of the group **initialization**, **key** establishment, and ...
<u>Cited by 146</u> - <u>Related Articles</u> - <u>View as HTML</u> - <u>Web Search</u>

### Remote **password** authentication scheme based on cross-product - group of 3 »
K Tan, H Zhu - Computer Communications, 1999 - inf.ufsc.br
... Then compute a public **key** matric: ... p□i; j □ 1; 2; ...; n□. Remote **password**
authentication
always includes three phases: card **initialization** phase, log ...
<u>Cited by 14</u> - <u>Related Articles</u> - <u>View as HTML</u> - <u>Web Search</u>

### Method of conducting secure operations on an uncontrolled network - group of 3 »
DL Denslow - US Patent 5,548,721, 1996 - Google Patents